## Econopak - Linkage Sprayer



## MODEL SPECIFICATIONS

PUMP	Silvan self-priming oil-backed diaphragm type with nitrile diaphragms and cast anodised aluminium body. BP60/20: 58 L/min. capacity 2000kPa pressure.		
воом	Econopak boom: 6m with stainless steel spray lines, non-drip nozzle holders, fully galvanised frame and spring loaded safety break back/forward.		
NOZZLES	Air induction nozzles with strainer in bayonet fit non-drip nozzle holders at 50cm spacings.		
CONTROLS	3 outlet manual control valve with pressure regulator. Mounted forward for easy access.		
TANK	Polytuff impact resistant polyethylene construction, moulded litre calibrations and non-spill screw-down lid with single breather.		

FRAME	Fully galvanised steel, cat I & II linkage.				
AGITATION	Bypass agitation.				
PRESSURE GAUGE	0-25 Bar dual stage glycerine filled gauge.				
FILTRATION	Lid strainer, suction line strainer and nozzle strainers.				
HOSE REEL	Fitted with rear-mounted Eco hosereel, 30m of 10mm hose and Spotjet spraygun with adjustable spray nozzle.				
PTO DRIVESHAFT	Quality driveshaft with quick release pins & safety cover.				
DIMENSIONS	L (MM)	W (MM)	Н (ММ)	KG (DRY)	
KBC300 (WITH BOOM)	1105	2067	1070	116	
KBC400 (WITH BOOM)	1105	2067	1310	121	
KBC600 (WITH BOOM)	1200	2067	1400	151	

MODEL DESCRIPTION		
300L ECONOPAK LINKAGE SPRAYER: BP60/20 pump, reel, hose & gun, 6m Econopak boom		
400L ECONOPAK LINKAGE SPRAYER: BP60/20 pump, reel, hose & gun, 6m Econopak boom		
600L ECONOPAK LINKAGE SPRAYER: BP60/20 pump, reel, hose & gun, 6m Econopak boom		
OPTIONS*	CODE	
14L foam marker (single side)	K99-31	
16L foam marker (double side)		
*Note: Dealer fitment. \$500 charge applies for factory fitment.		