

# Super 800/1100L - Linkage Sprayer



Pictured: 1100L with BP125/20 pump and optional flush tank



Pictured: 800L with BP125/20 pump

| MODEL SPECIFICATIONS      |   |               |               |                 |
|---------------------------|---|---------------|---------------|-----------------|
| <b>PUMP</b>               | Silvan self-priming oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body with raised pump mount.<br>BP75/20: 71L/min. capacity 2000kPa pressure.<br>BP125/20: 121L/min. capacity 2000kPa pressure.   |               |               |                 |
| <b>CONTROLS</b>           | 3 outlet manual control valve with pressure regulator.  |               |               |                 |
| <b>TANK</b>               | Low profile, 800 and 1100L Polytuff impact resistant polyethylene construction, external sightline with floating ball and non-spill offset screw-down lid with single breather. 15L freshwater tank with screw-down lid and on/off tap. 4L toolbox with polythylene lid. 50mm Camlock bottom fill (1100L only). |               |               |                 |
| <b>FRAME</b>              | Galvanised steel, with adjustable cat II hitch. Vertical boom channel positions boom at optimum spray height.   |               |               |                 |
| <b>AGITATION</b>          | Bypass agitation.   |               |               |                 |
| <b>CHEMICAL INDUCTION</b> | 1100L: Venturi suction probe with detachable hose.  |               |               |                 |
| <b>PRESSURE GAUGE</b>     | 0-25 Bar dual stage glycerine filled gauge.   |               |               |                 |
| <b>FILTRATION</b>         | Lid strainer, suction line strainer with stop valve fitted at the side of the tank to enable ease of filter maintenance.  |               |               |                 |
| <b>PTO DRIVESHAFT</b>     | Quality driveshaft with quick release pins & safety cover.  |               |               |                 |
| <b>DIMENSIONS</b>         | <b>L (MM)</b>   | <b>W (MM)</b> | <b>H (MM)</b> | <b>KG (DRY)</b> |
| K08N-75 (LESS BOOM)       | 1350  | 1395          | 1315          | 145             |
| K11NH-75 (LESS BOOM)      | 1350  | 1395          | 1610          | 160             |

| MODEL DESCRIPTION   | CODE        |
|---|-------------|
| 800L LINKAGE: BP75/20 pump, no boom   | K08N-75     |
| 800L LINKAGE: BP125/20 pump, no boom  | K08N-125    |
| 1100L LINKAGE: BP75/20 pump, no boom  | K11NH-75    |
| 1100L LINKAGE: BP125/20 pump, no boom   | K11NH-125   |
| FACTORY OPTIONS*  | CODE        |
| 6m Field boom   | 032-044-6   |
| 8m Field boom   | 032-044-8   |
| 10m Field boom  | 032-044-10  |
| 6m Devil boom with hydraulic fold   | 032-19D     |
| 8m Devil boom with hydraulic fold   | 032-25D     |
| 10m Devil boom with hydraulic fold  | 032-32DM    |
| 10m HD Devil boom with hydraulic fold   | 032-32D     |
| 12m HD Devil boom with hydraulic fold**   | 032-40D     |
| 14m HD Devil boom with hydraulic fold**   | 032-48D     |
| 15m HD Devil boom with hydraulic fold**   | 032-50D     |
| Hydraulic lift, galvanised single hydraulic system - 6, 8 & 10m devil booms                   | 032-19DL    |
| Hydraulic lift, galvanised single hydraulic system - 10, 12, 14 & 15m HD Devil booms          | 032-40DL    |
| Hydraulic lift with airbag suspension - 10, 12, 14 & 15m HD Devil booms                       | 032-40DLAB  |
| 8 Jet vine boom (Used with BP60/20 pump only)   | 032-G       |
| 10 Jet vine boom (Used with BP60/20 pump only)  | 032-H       |
| Olive boom (Use with BP125/20 pump only)  | 032-R       |
| Undervine and mid row boom  | 032-HERB    |
| Boomless nozzle mounting kit (brass nozzle not included)                                      | K99-10      |
| 70L flush tank kit to flush the filter, spraylines and nozzles                                | K99-47      |
| 16L foam marker (double side)   | K99-39      |
| 57L Paddock marker foam marker  | K99-43      |
| Economy hosereel, 20m hose (10mm ID) & Triam spraygun   | 180E02012CT |
| Reel tuff 12V remote reel with Turbo 400 spray gun  | K99-51      |
| Electric on/off control 3 section   | K99-34      |
| Electric control 3 section with in cab pressure adjustment                                    | K99-29      |
| Bravo 180S automatic rate controller  | J99-151     |
| Silmix chemical hopper  | K99-21      |
| <b>Note: Not all options will fit all models. Extra charges may apply to fitment.</b>         |             |
| <b>** If fitting 12, 14 &amp; 15m HD Devil boom to a 800L TPL add \$800 for heavier frame</b> |             |